

CILINDROS NEUMATICOS

ACCESORIOS ISO 15552

ART. EN ESCUADRA ISO15552



Referencia: **CD/AS50**

Descripción

Articulación en escuadra

Características

| RefeØ<br>rencmm<br>ia | CK | EM | BR   | PH  | GL  | ØHBLB | BT   | TE | RA  | ØD | LD | UL | UR  | EA  |    |
|-----------------------|----|----|------|-----|-----|-------|------|----|-----|----|----|----|-----|-----|----|
| CD/AS32<br>32         | 10 | 26 | 10   | 32  | 21  | 6.6   | 6.4  | 8  | 38  | 18 | 21 | 3  | 51  | 31  | 10 |
| CD/AS40<br>40         | 12 | 28 | 11   | 36  | 24  | 6.6   | 8.4  | 10 | 41  | 22 | 21 | 3  | 54  | 35  | 15 |
| CD/AS50<br>50         | 12 | 32 | 13   | 45  | 33  | 9     | 10.4 | 12 | 50  | 30 | 21 | 3  | 65  | 45  | 16 |
| CD/AS63<br>63         | 16 | 40 | 15   | 50  | 37  | 9     | 12.4 | 14 | 52  | 35 | 21 | 3  | 67  | 50  | 16 |
| CD/AS80<br>80         | 16 | 50 | 15   | 63  | 47  | 11    | 11.5 | 14 | 66  | 40 | 21 | 3  | 86  | 60  | 20 |
| CD/AS100<br>100       | 20 | 60 | 19   | 71  | 55  | 11    | 14.5 | 17 | 76  | 50 | 11 | 3  | 96  | 70  | 20 |
| CD/AS125<br>125       | 25 | 70 | 22.5 | 90  | 70  | 14    | 16.8 | 20 | 94  | 60 | 21 | 3  | 124 | 90  | 30 |
| CD/AS160<br>160       | 30 | 90 | 31.5 | 115 | 97  | 14    | 21   | 25 | 118 | 88 | 31 | 5  | 156 | 126 | 36 |
| CD/AS200<br>200       | 30 | 90 | 31.5 | 135 | 105 | 18    | 26   | 30 | 122 | 90 | 31 | 5  | 162 | 130 | 40 |

