

COMPONENTI TIPO O FILETTO M5

- ① Spillo in ottone
- ② Bussola in ottone nichelato
- ③ Corpo in ottone nichelato
- ④ Anello di fermo in ottone nichelato
- ⑤ Guarnizione in NBR
- ⑥ Anello girevole in ottone nichelato o tecnopolimero
- ⑦ Guarnizione in NBR
- ⑧ Anello sostegno molla in tecnopolimero
- ⑨ Molla di aggraffaggio in acciaio inossidabile
- ⑩ Bussola di fermo in tecnopolimero
- ⑪ Bussola di sgancio in tecnopolimero

TYPE O COMPONENTS M5 THREAD


- ① Brass pin
- ② Nickel-plated brass bush
- ③ Nickel-plated brass body
- ④ Nickel-plated brass retaining ring
- ⑤ NBR gasket
- ⑥ Nickel-plated or technopolymer brass revolving ring
- ⑦ NBR gasket
- ⑧ Technopolymer spring supporting ring
- ⑨ Stainless steel grabbing spring
- ⑩ Technopolymer retaining bush
- ⑪ Technopolymer release bush

Cod.	F	F2	CH	A min	A max	A1	B	C	D	E	I	Conf.
HREG1/8	1/8	1/8	12	29.8	30.9	34	21.4	6	9.8	13.3	6.7	10
HREG1/4	1/4	1/4	15	35.4	37	38.9	25.5	8	11.1	16.7	8	10

HREG



- MRF regolazione cacciavite
- Restriction valve screw driver regulation



- Cilindro
- Cylindre

