

MANOMETROS

SECOS

M.SECO Ø40 1/8 POS. 0-16 BAR/PSI



Referencia: **M4016**

Descripción

Manómetro seco de salida roscada central posterior. La rosca es de tipo cónico ISO 7/l.

Características

| Referencia | F | Rango (bar) | A | C | P |
|------------|-----|-------------|----|----|----|
| M4001,6 | 1/8 | 0-1,6 | 40 | 40 | 10 |
| M4002,5 | 1/8 | 0-2,5 | 40 | 40 | 10 |
| M4004 | 1/8 | 0-4 | 40 | 40 | 10 |
| M4006 | 1/8 | 0-6 | 40 | 40 | 10 |
| M4010 | 1/8 | 0-10 | 40 | 40 | 10 |
| M4012 | 1/8 | 0-12 | 40 | 40 | 10 |
| M4016 | 1/8 | 0-16 | 40 | 40 | 10 |
| M4025 | 1/8 | 0-25 | 40 | 40 | 10 |
| M5001,6 | 1/8 | 0-1,6 | 50 | 46 | 10 |
| M5002,5 | 1/8 | 1-2,5 | 50 | 46 | 10 |
| M5004 | 1/8 | 0-4 | 50 | 46 | 10 |
| M5006 | 1/8 | 0-6 | 50 | 46 | 10 |
| M5010 | 1/8 | 0-10 | 50 | 46 | 10 |
| M5012 | 1/8 | 0-12 | 50 | 46 | 10 |
| M5016 | 1/8 | 0-16 | 50 | 46 | 10 |
| M5025 | 1/8 | 0-25 | 50 | 46 | 10 |
| M6301,6 | 1/4 | 0-1,6 | 63 | 50 | 12 |
| M6302,5 | 1/4 | 0-2,5 | 63 | 50 | 12 |
| M6304 | 1/4 | 0-4 | 63 | 50 | 12 |
| M6306 | 1/4 | 0-6 | 63 | 50 | 12 |
| M6310 | 1/4 | 0-10 | 63 | 50 | 12 |
| M6312 | 1/4 | 0-12 | 63 | 50 | 12 |
| M6316 | 1/4 | 0-16 | 63 | 50 | 12 |
| M6325 | 1/4 | 0-25 | 63 | 50 | 12 |

