

MANOMETROS

SECOS

M.SECO Ø63 1/4 POS. 0-25 BAR/PSI



Referencia: **M6325**

Descripción

Manómetro seco de salida roscada central posterior. La rosca es de tipo cónico ISO 7/l.

Características

Referencia	F	Rango (bar)	A	C	P
M4001,6	1/8	0-1,6	40	40	10
M4002,5	1/8	0-2,5	40	40	10
M4004	1/8	0-4	40	40	10
M4006	1/8	0-6	40	40	10
M4010	1/8	0-10	40	40	10
M4012	1/8	0-12	40	40	10
M4016	1/8	0-16	40	40	10
M4025	1/8	0-25	40	40	10
M5001,6	1/8	0-1,6	50	46	10
M5002,5	1/8	1-2,5	50	46	10
M5004	1/8	0-4	50	46	10
M5006	1/8	0-6	50	46	10
M5010	1/8	0-10	50	46	10
M5012	1/8	0-12	50	46	10
M5016	1/8	0-16	50	46	10
M5025	1/8	0-25	50	46	10
M6301,6	1/4	0-1,6	63	50	12
M6302,5	1/4	0-2,5	63	50	12
M6304	1/4	0-4	63	50	12
M6306	1/4	0-6	63	50	12
M6310	1/4	0-10	63	50	12
M6312	1/4	0-12	63	50	12
M6316	1/4	0-16	63	50	12
M6325	1/4	0-25	63	50	12

