

MANOMETROS

SECOS

M.PANEL F.POS. Ø50 1/8 0-10 BAR/PSI



Referencia: **MPF5010**

Descripción

Manómetro seco con empotrable mediante estribo posterior con salida roscada posterior y doble escala (bar/Psi). La rosca es de tipo cónico ISO 7/I.

Características

| Referencia | F | Rango (bar) | A | D | P |
|------------|-----|-------------|----|----|----|
| MPF4001,6 | 1/8 | 0-1,6 | 27 | 40 | 10 |
| MPF4002,5 | 1/8 | 0-2,5 | 27 | 40 | 10 |
| MPF4004 | 1/8 | 0-4 | 27 | 40 | 10 |
| MPF4006 | 1/8 | 0-6 | 27 | 40 | 10 |
| MPF4010 | 1/8 | 0-10 | 27 | 40 | 10 |
| MPF4012 | 1/8 | 0-12 | 27 | 40 | 10 |
| MPF5001,6 | 1/8 | 0-1,6 | 29 | 50 | 10 |
| MPF5002,5 | 1/8 | 0-2,5 | 29 | 50 | 10 |
| MPF5004 | 1/8 | 0-4 | 29 | 50 | 10 |
| MPF5006 | 1/8 | 0-6 | 29 | 50 | 10 |
| MPF5010 | 1/8 | 0-10 | 29 | 50 | 10 |
| MPF5012 | 1/8 | 0-12 | 29 | 50 | 10 |
| MPF6301,6 | 1/4 | 0-1,6 | 30 | 62 | 12 |
| MPF6302,5 | 1/4 | 0-2,5 | 30 | 62 | 12 |
| MPF6304 | 1/4 | 0-4 | 30 | 62 | 12 |
| MPF6306 | 1/4 | 0-6 | 30 | 62 | 12 |
| MPF6310 | 1/4 | 0-10 | 30 | 62 | 12 |
| MPF6312 | 1/4 | 0-12 | 30 | 62 | 12 |

