

MANOMETROS

SECOS

M.SECO Ø50 1/4 RAD. 0-10 BAR/PSI



Referencia: **MR5010**

Descripción

Manómetro seco de salida roscada radial inferior. La rosca es de tipo cónico ISO 7/l.

Características

Referencia	F	Rango (bar)	A	B	C	P
MR4001,6	1/8	0-1,6	40	26	26	10
MR4002,5	1/8	0-2,5	40	26	26	10
MR4004	1/8	0-4	40	26	26	10
MR4006	1/8	0-6	40	26	26	10
MR4010	1/8	0-10	40	26	26	10
MR4012	1/8	0-12	40	26	26	10
MR4016	1/8	0-16	40	26	26	10
MR4025	1/8	0-25	40	26	26	10
MR5001,6	1/4	0-1,6	50	27	33	12
MR5002,5	1/4	0-2,5	50	27	33	12
MR5004	1/4	0-4	50	27	33	12
MR5006	1/4	0-6	50	27	33	12
MR5010	1/4	0-10	50	27	33	12
MR5012	1/4	0-12	50	27	33	12
MR5016	1/4	0-16	50	27	33	12
MR5025	1/4	0-25	50	27	33	12
MR6301,6	1/4	0-1,6	63	29	38	12
MR6302,5	1/4	0-2,5	63	29	38	12
MR6304	1/4	0-4	63	29	38	12
MR6306	1/4	0-6	63	29	38	12
MR6310	1/4	0-10	63	29	38	12
MR6312	1/4	0-12	63	29	38	12
MR6316	1/4	0-16	63	29	38	12
MR6325	1/4	0-25	63	29	38	12

