

# MANOMETROS

## SECOS

M.SECO Ø63 1/4 RAD. 0-2,5 BAR/PSI



Referencia: **MR6302,5**

### Descripción

Manómetro seco de salida roscada radial inferior. La rosca es de tipo cónico ISO 7/l.

### Características

| Referencia F |     | Rango (bar)A |    | B  | C  | P  |
|--------------|-----|--------------|----|----|----|----|
| MR4001,6     | 1/8 | 0-1,6        | 40 | 26 | 26 | 10 |
| MR4002,5     | 1/8 | 0-2,5        | 40 | 26 | 26 | 10 |
| MR4004       | 1/8 | 0-4          | 40 | 26 | 26 | 10 |
| MR4006       | 1/8 | 0-6          | 40 | 26 | 26 | 10 |
| MR4010       | 1/8 | 0-10         | 40 | 26 | 26 | 10 |
| MR4012       | 1/8 | 0-12         | 40 | 26 | 26 | 10 |
| MR4016       | 1/8 | 0-16         | 40 | 26 | 26 | 10 |
| MR4025       | 1/8 | 0-25         | 40 | 26 | 26 | 10 |
| MR5001,6     | 1/4 | 0-1,6        | 50 | 27 | 33 | 12 |
| MR5002,5     | 1/4 | 0-2,5        | 50 | 27 | 33 | 12 |
| MR5004       | 1/4 | 0-4          | 50 | 27 | 33 | 12 |
| MR5006       | 1/4 | 0-6          | 50 | 27 | 33 | 12 |
| MR5010       | 1/4 | 0-10         | 50 | 27 | 33 | 12 |
| MR5012       | 1/4 | 0-12         | 50 | 27 | 33 | 12 |
| MR5016       | 1/4 | 0-16         | 50 | 27 | 33 | 12 |
| MR5025       | 1/4 | 0-25         | 50 | 27 | 33 | 12 |
| MR6301,6     | 1/4 | 0-1,6        | 63 | 29 | 38 | 12 |
| MR6302,5     | 1/4 | 0-2,5        | 63 | 29 | 38 | 12 |
| MR6304       | 1/4 | 0-4          | 63 | 29 | 38 | 12 |
| MR6306       | 1/4 | 0-6          | 63 | 29 | 38 | 12 |
| MR6310       | 1/4 | 0-10         | 63 | 29 | 38 | 12 |
| MR6312       | 1/4 | 0-12         | 63 | 29 | 38 | 12 |
| MR6316       | 1/4 | 0-16         | 63 | 29 | 38 | 12 |
| MR6325       | 1/4 | 0-25         | 63 | 29 | 38 | 12 |

